



Kjennetegn

Image not found or type unknown

Twin KPL luftgardin

- Specially designed to be installed on doors of industrial cold stores and freezers with big temperature differences.
- The Twin Kool air curtain system has been designed to offer a versatile solution for any type of cold room. It has two jets of opposing air chambers that create additional space between the chamber and the pre-chamber. Thanks to the double barrier, this model becomes the perfect alternative to the TRIOJET SYSTEM air curtain when space is limited or this model is not an option.
- Selvbærende konstruksjon av foringsrør, laget av galvaniserte stålplater., fullført i strukturell epoxy-polyester maling hvit farge RAL9016 som standard. Andre farger eller rustfritt stål er tilgjengelig ved forespørsel.
- Stort fasettert innløpsgitter som unngår intensivt vedlikehold.
- Anodiserte utløpsskovler av aluminium, vingeformet, justerbar fra 0 til 15° på hver side.
- Sentrifugalvifter med dobbelt innløp, drevet av en ekstern rotormotor og lavt støynivå. 5-trinnsvelger. EC modeller satt sammen med svært effektive vifter med lavt forbruk.
- “A” type uten oppvarming, kun luft.
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 7m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
 - Auxiliary temperature sensors that improve air curtain control and increase energy savings.
 - Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.
- Includes varnishing on the PCB to protect it from corrosion.

Spesifikasjoner

50Hz

Ikke varmet		
Modell	(m²/h)	(m)
TWIN KPL M 1500 A	9,8-13,1	
TWIN KPL M 2000 A	9,8-13,1	
TWIN KPL M 2500 A	9,8-13,1	
TWIN KPL M 3000 A	9,8-13,1	
TWIN KPL ECM 1500 A	9,8-13,8	
TWIN KPL ECM 2000 A	9,8-13,8	
TWIN KPL ECM 2500 A	9,8-13,8	
TWIN KPL ECM 3000 A	9,8-13,8	
TWIN KPL G 1500 A	9,8-13,1	
TWIN KPL G 2000 A	9,8-13,1	
TWIN KPL G 2500 A	9,8-13,1	
TWIN KPL G 3000 A	9,8-13,1	
TWIN KPL ECG 1500 A	9,8-13,8	
TWIN KPL ECG 2000 A	9,8-13,8	
TWIN KPL ECG 2500 A	9,8-13,8	
TWIN KPL ECG 3000 A	9,8-13,8	

60Hz

Ikke varmet



Modell	(m³/h)	(m)
TWIN KPL ECM 1500 A	9,8-13,8	
TWIN KPL ECM 2000 A	9,8-13,8	
TWIN KPL ECM 2500 A	9,8-13,8	
TWIN KPL ECM 3000 A	9,8-13,8	
TWIN KPL ECG 1500 A	9,8-13,8	
TWIN KPL ECG 2000 A	9,8-13,8	
TWIN KPL ECG 2500 A	9,8-13,8	
TWIN KPL ECG 3000 A	9,8-13,8	

Dimensjoner

Twin KPL luftgardin - Dimensjoner